



ALLIANCE  
AGRICULTURE  
  
TRA: I-2  
Speed Rating: D

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction characteristics to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can drive upto 100 km/h and are best suited for tough applications compared to the standard range.

HEAVY DUTY FLOTATION - 600/60R30.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed Application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
600/60R30.5	AG 20.00	24.8	59.4	27.4	182.1	178D	12	13450	10520	9240	8820	7940	7080	6260	5840
							17	17040	13340	11710	11180	10080	8970	7940	7410
							22	19380	15170	13320	12720	11460	10190	9020	8420
							23	20130	15760	13820	13210	11910	10580	9370	8750
							29	22930	17950	15740	15060	13560	12060	10670	9970
							35	25510	19950	17530	16760	15080	13430	11860	11090
							41	27930	21870	19200	18340	16510	14710	13010	12150
							46	30230	23660	20770	19840	17880	15900	14070	13140
							52	32410	25350	22270	21280	19160	17040	15080	14090
							58	34480	26990	23680	22640	20390	18140	16050	14990
							64	36460	28530	25040	23940	21560	19180	16950	15850
							73	37570	29410	25820	24670	22220	19780	17480	16340
							87	38030	29760	26130	24980	22490	20020	17700	16540

