



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-4
Speed Rating: A8

Alliance 500 is a modern radial tire for industrial tractors. The tire displays high traction, braking, mileage, riding comfort in transport applications and better resistance to the penetration of sharp objects. All this is achieved by a radial nylon casing, a tough rayon belt, trash shields and a unique self-cleaning tread design.

INDUSTRIAL TRACTOR - 17.5LR24

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
		Constant load						Cyclic Applications								
SW inch	OD inch	Static mph	6 mph	19 mph	25 mph	31 mph	6 mph	19 mph	25 mph	31 mph						
17.5LR24	W15L W14L	17.5	48.8	21.6	142.3	** 139A8	22	11050	6020	4890	4810	4370	7210	5140	4810	4370
							23	11510	6260	5120	5000	4560	7520	5360	5000	4560
							26	12320	6700	5470	5360	4870	8050	5730	5360	4870
						145A8	29	12940	7030	5730	5620	5120	8440	6020	5620	5120
							32	13650	7410	6040	5930	5400	8910	6350	5930	5400
							36	14710	8000	6530	6390	5820	9590	6830	6390	5820
						150A8	38	15610	8490	6920	6790	6170	10190	7280	6790	6170
							41	16340	8890	7230	7100	6460	10650	7610	7100	6460
							44	17000	9240	7540	7390	6720	11090	7890	7390	6720

The Size 17.5LR24 (LI - 139A8) is no longer active for production

