



**GALAXY
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **A8**



The Galaxy Earth-Pro 800 Radial R-1W Agricultural Radial offers a complete range of front and rear tractor tire combinations. The pads between the lugs, apart from adding strength to the tire, act as mud breakers to enhance their self-cleaning characteristics. The reinforced lug, bead areas and the improved tread compound, used in the tire, provide longer life of the tires. A smooth ride both on & off road is enabled by the multi-angle lug design with steep angle in the center. The shallow angle at shoulder and higher NSD provides superior traction.

TRACTOR - 480/80R42

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
		Drive wheel application												
		31 mph	Static mph					3 mph	9 mph	12 mph	19 mph	25 mph		
480/80R42	DW16LX42 W16LX42, , W15LX42 DW15LLX42, , W14LX42	18.9	72.2	32.9	215.7	151A8 151B	12	4810	11050	8170	6440	5910	5140	4810
							17	6170	14200	10490	8270	7590	6610	6170
							20	6950	15970	11810	9310	8540	7430	6950
							23	7610	17490	12930	10190	9360	8140	7610

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
		Drive wheel application												
		31 mph	Static mph					3 mph	9 mph	12 mph	19 mph	25 mph		
480/80R42	DW16LX42 W16LX42, , W15LX42 W14LX42, , DW14LX42	18.9	72.2	32.9	215.7	151A8 151B	12	4810	11050	8170	6440	5910	5140	4810
							17	6170	14200	10490	8270	7590	6610	6170
							20	6950	15970	11810	9310	8540	7430	6950
							23	7610	17490	12930	10190	9360	8140	7610

