

ALLIANCE
EARTHMOVER & MINING

TRA: **E-2/L-2/G-2**
Speed Rating: **B**

Alliance 600 is a modern wide base, all steel radial tire for all types of earthmoving equipments. Its unique tread design and sophisticated construction ensure superior performance coupled with smoother rides and higher productivity

LOADER DOZER - 15.5R25 L2

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
15.5R25 L2	12.00/1.3	15.4	50.2	22.7	148.0	* 169A2	51	17680	12480	11050	9390
							58	19090	13470	11930	10140
							65	20460	14440	12790	10870

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
15.5R25 L2	12.00/1.3	15.4	50.2	22.7	148.0	* 169A2	61	19890	16010	14900	13800
							70	21470	17280	16090	14900
							78	23020	18540	17260	15980

Speed:10km/h (5mph); Distance:up to 76km (250 miles) - one way