

ALLIANCE
CONSTRUCTION & INDUSTRIAL

TRA: **R-4**
Speed Rating: **D**

Alliance 606 tire for Loaders and Dozers is a low section tire for light earthmoving equipment. The tire is an all steel radial tire with steel belted construction. The unique non-directional tread design suits on/off road services. High mileage, easy self cleaning, best traction, fuel saving and ride comfort are some of its advantages.

EM - 335/80R18

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
335/80R18	11	14.6	38.7	17.4	114.2	145A2	33	7580	5360	4740	4030
							36	8070	5710	5050	4300
							40	8530	6020	5340	4540
							44	9000	6350	5620	4780
							47	9410	6660	5890	5000
							51	9830	6950	6150	5230
							54	10230	7230	6390	5450

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
335/80R18	11	14.6	38.7	17.4	114.2	145A2	39	8530	6880	6390	5930
							44	9080	7320	6810	6310
							48	9610	7740	7210	6680
							52	10120	8160	7580	7030
							57	10600	8530	7940	7360
							61	11070	8930	8310	7690
							65	11510	9280	8640	8000

Recommended rim in red