



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-4
Speed Rating: D

Alliance 606 tire for Loaders and Dozers is a low section tire for light earthmoving equipment. The tire is an all steel radial tire with steel belted construction. The unique non-directional tread design suits on/off road services. High mileage, easy self cleaning, best traction, fuel saving and ride comfort are some of its advantages.

EM - 335/80R20EM(12.5R20)

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Off-the road									
		Static mph	3 mph					6 mph	16 mph		
335/80R20EM(12.5R20)	11SDC 12SDC	14.4	42.4	18.7	123.2	147A2	33	8050	5690	5030	4280
							36	8580	6060	5360	4560
							40	9040	6370	5640	4810
							44	9520	6720	5950	5070
							47	9990	7060	6240	5310
							51	10410	7340	6500	5530
							54	10850	7650	6780	5750
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
		Hard Improved Surfaces									
		Static mph	3 mph					6 mph	16 mph		
335/80R20EM(12.5R20)	11SDC 12SDC	14.4	42.4	18.7	123.2	147A2	39	9040	7300	6790	6280
							44	9630	7760	7230	6700
							48	10160	8180	7630	7060
							52	10710	8640	8050	7450
							57	11220	9040	8420	7800
							61	11710	9440	8770	8140
							65	12210	9830	9150	8470

Recommended rim in red

