

ALLIANCE
EARTHMOVER & MINING

TRA: **E-3/G-3/L-3**
Speed Rating: **B**

Alliance 650 has a well proven tread pattern that enables its use for a wide range of applications on different kinds of mobile construction equipments. Its all steel construction ensures higher productivity with lower downtime.

LOADER DOZER - 23.5R25 L-3/E3

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
23.5R25 L-3/E3	19.50/2.5	24.2	63.7	28.3	186.2	** 201A2	44	34970	24690	21850	18560
							51	38270	27030	23920	20330
							58	41380	29210	25860	21980
							73	47140	33290	29450	25040
							83	51150	36130	31970	27180

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		SW inch	OD inch					Static mph	3 mph	6 mph	16 mph
23.5R25 L-3/E3	19.50/2.5	24.2	63.7	28.3	186.2	** 201A2	52	39330	31680	29500	27320
							61	43060	34680	32300	29900
							70	46540	37500	34920	32320
							87	53020	42700	39770	36820
							100	57540	46360	43170	39970

Highlighted rows indicate grader application
Speed:10 Km/h (5 mph); Distance:up to 76 m (250 feet) - one way