




ALLIANCE
AGRICULTURE

TRA: **R-1W**
 Speed Rating: **A8**



FarmPro 90 is engineered with a multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall

TRACTOR - 320/90R46(12.4R46)

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
		Cyclic operation						Non cyclic operation								
		6 mph	9 mph					Static mph	6 mph	9 mph	16 mph	19 mph	25 mph	31 mph		
320/90R46(12.4R46)	W10X46 W11X46, W9X46	12.6	68.7	32.3	205.8	148A8 148B	12	NA	NA	6900	4500	4010	3330	3220	3000	3000
							15	2310{hlc}	2110{hlc}	NA	NA	NA	NA	NA	NA	NA
							17	NA	NA	8890	5800	5180	4280	4120	3860	3860
							22	6570	5980	NA	NA	NA	NA	NA	NA	NA
							29	NA	NA	11970	7800	6970	5780	5580	5200	5200
							36	8840	8070	NA	NA	NA	NA	NA	NA	NA
							41	NA	NA	14200	9260	8270	6860	6610	6170	6170
							51	10490	9570	NA	NA	NA	NA	NA	NA	NA
							52	NA	NA	15980	10430	9300	7720	7430	6950	6950
65	11820	10760	NA	NA	NA	NA	NA	NA	NA							

