



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: E-2/L-2/G-2
Speed Rating: A8

Alliance 302 Industrial Implement tire is a heavy duty implement tire for industrial application and for all types of hard surfaces. It has good self-cleaning ability, as well as high traction, which makes this tread design suitable for all kinds of off road services. Its strong nylon carcass ensures full power transmission as well as good resistance to mechanical tire failures.

TRACTOR HEAVY DUTY - 14.9-28

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Industrial Use			
		Constant load						Cyclic Application			
		12 mph	25 mph					12 mph	25 mph		
14.9-28	W13 W12	14.9	52.9	23.9	156.0	8PR	22	4920	4520	5560	4520
						140A8	26	5490	5030	6170	5030
							30	6020	5510	6790	5510
						12PR	36	6680	6130	7540	6130
						148A8	41	7140	6550	8050	6550
							45	7560	6950	8530	6950
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Agricultural Use			
		Field	Road Transport								
		6 mph	12 mph					25 mph	31 mph		
14.9-28	W13 W12	14.9	52.9	23.9	156.0	8PR	19	4630	4630	3460	3150
						140A8	23	5230	5230	3900	3550
							26	5620	5620	4190	3810
						12PR	30	4810	6020	4500	4100
						148A8	35	5180	6500	4850	4410
							39	5580	6970	5200	4740



Note : For above mentioned size only 12 PR is active for production.