



ALLIANCE  
AGRICULTURE  
  
TRA: F-2  
Speed Rating: A8

FarmPRO 303 is an aesthetically improved modern F-2 design. It has an optimized rib design suitable for both on and off-road applications. The specially designed ribs ensure better readability. An additional rubber layer under the tread provides penetration resistance while improved sidewall deflection on loading ensures better stability.

TRACTOR - 7.50-16

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
		SW inch	OD inch					Speed				
								6 mph	12 mph	16 mph	19 mph	25 mph
7.50-16	5.50FX16	8.1	31.7	14.2	96.1	6PR	29	2030	1650	1430	1350	1080
						98A6/90A8	32	2160	1760	1540	1430	1150
							36	2320	1900	1650	1540	1240
							41	2490	2230	1900	1650	1320
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
		SW inch	OD inch					Speed				
								6 mph	12 mph	16 mph	19 mph	25 mph
7.50-16	5.50FX16	8.1	31.7	15.0	96.9	8PR	39	2430	1980	1720	1610	1280
						103A6/96A8	44	2580	2120	1830	1720	1370
							48	2710	2230	1940	1810	1460
							54	2890	2600	2230	1930	1540

Highlighted column indicates (1) 6 PR and above with a 25% increase in inflation pressure. (2) In case where a front-end loader is fitted on the tractor, +100% applies.

