



GALAXY
EARTHMOVER &
MINING

TRA: E-4
Speed Rating: B

Galaxy HTSR 400 is specially built for machines that face extreme environments while hauling heavy loads. High tread depth ensures consistent traction and greater cut resistance making it the more productive choice. Understanding that each job site is different and has distinct needs HTSR 400 comes with variants of compounds like regular, cut-resistant, and heat-resistant. Whether it is to get minimum heat build-up while performing longer runs, or superior cut & chip protection while plying through rough uneven surfaces. We have got it covered. HTSR 400 is designed with the ultimate aim of providing excellent durability resulting in reduced downtime.

Articulated Dump Trucks - 29.5R25

Size	Pattern	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	NSD 1/32 inch	TKPH/ TMPH	Maximum Speed	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
			SW inch	OD inch							Star Mark										***	
											Psi	40	44	47	51	54	58	62	65	69	73	76
29.5R25	HTSR400	25.00/3.5-25	30.1	74.4	33.5	220.9	200B 216A2	2.34	0 TMPH	0 KMPH	lbs	18739	20393	21495	22708	24030	25353	26015	27558	28329	29983	30865

“This size is available in HRC, CRC and REG compounds.”

