



**GALAXY**  
**AGRICULTURE**

TRA: **IMP**  
 Speed Rating: **A8**

Alliance 320 is a low-section implement tire with high load capacity and minimum soil compaction. This is an ideal tire for modern farming designed for on and off road applications. Its strong nylon construction provides superior performance and durability.

**IMPLEMENT - 10.0/75-15.3**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
		SW inch	OD inch					Speed							
								Drive Wheel				Free Rolling			
								6 mph	16 mph	25 mph	31 mph	6 mph	16 mph	25 mph	31 mph
10.0/75-15.3	9	10.4	29.9	13.5	88.3	8	22	1850	1570	1320	1190	2650	2250	1900	1700
						118A8	41	2690	2290	1920	1720	3840	3260	2730	2470
						105A8	45	2870	2430	2040	1830	4080	3460	2910	2620
						101B	61	4100	3460	2910	2620	4890	4150	3480	3150

Highlighted rows indicate cyclic high load variations. Note: For above mentioned size 8 PR is no longer active for production. 1) When tires equip vehicles subject to haulage cyclic high load variations excluding transport application on long distances, i.e. vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). 2) When fitted on tractor steering wheels load capacities are 80% of free rolling and inflation pressure 20% higher. 3) For 10 km/h and stationary use inflation pressure raised 20% and 25% respectively.

