



**ALLIANCE
AGRICULTURE**

TRA: IMP
Speed Rating: A8

A 320 Value Plus is specially designed for agricultural implements. Its large footprint high rubber to void ratio minimizes soil compaction. Strong textile construction ensures optimal performance and long tire life. This tire can be used on roads and also for grassland and sensitive soil applications in the fields.

IMPLEMENT - 10.0/75-15.3

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load														
		Speed										Drive wheel					Free rolling					
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	Static mph	6 mph	16 mph	19 mph	25 mph					
10.0/75-15.3	9	10.4	29.9	13.5	88.3	10PR	57	5640	3100	2570	2400	2160	5640	4410	3660	3420	3080					
						129A6 125A8	77	NA	NA	NA	NA	NA	6770	5290	4370	4080	3640					
						14PR	80	6830	3750	3110	2910	2620	6910	5400	4480	4190	3770					
						136A6 132A8	109	NA	NA	NA	NA	NA	8290	6490	5360	4940	4410					

Highlighted rows indicate cyclic high load variations. When tires equip vehicles subject to haulage cyclic high load variations excluding transport application on long distances, i.e. vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). Please note that the PR/LI corresponds to the HLV.

