

# AGRIFLEX+363

## SPECIALTY SPRAYER TIRE

### ON & OFF-ROAD IF/VF

### PERFORMANCE



- Engineered with Increased Flexion (IF) and Very Increased Flexion (VF) technology
- Provides up to 40% more load capacity than standard tires for higher productivity
- Allows up to a 40% decrease in tire pressure compared to standard tires, preventing soil compaction and field damage
- Unique tread design offering a smooth ride and long even wear
- High speed capabilities both on and off road – 40MPH
- Stubble guard compound for long tread life
- Steel belted tread area offering puncture resistance and a more uniformed footprint

R-1

D

H

O&O

**LARGE FOOTPRINT, LOW SOIL COMPACTION, GREAT TRACTION.  
INCREASED PRODUCTIVITY AND REDUCED COSTS.**



# AGRIFLEX+ 363 STEEL BELTED R-1

OEM FITMENT



The Alliance Agriflex+ 363 is rated for speeds up to 40 mph over the road, and is designed for sprayers that need to perform both on the fields and on the road. State-of-the-art materials and the steel-belted construction allow IF (Increased Flexion) radial tractor tires to deliver outstanding performance in any conditions. IF tires carry 20% more load on the same inflation pressure as conventional radials, or require 20% less inflation pressure for the same load, to reduce soil compaction. (TUBELESS - STEEL BELTED - STUBBLE GUARD)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
36350532	VF 270/95R32		138D		TL	44	W9	52.4	11.2	156.2	24.0	5200	35	40
36350462	VF 270/95R36		140D		TL	44	W9	56.1	10.9	168.8	26.0	5510	35	40
36350004	VF 270/95R38		141D		TL	44	W9	58.1	10.9	174.5	26.8	5670	35	40
36350020	VF 320/90R46		155D		TL	47	DW11	68.8	12.1	210.0	31.8	8540	41	40
36300036	VF 380/90R46	14.9R46	173D		TL	49	DW13	72.5	15.3	218.4	33.4	14300	64	40
36300011	VF 230/95R48	9.5R48	146D		TL	42	DW9	65.4	9.1	199.1	30.9	6600	52	40
36300014	VF 270/95R48	11.2R48	155D		TL	44	DW10	68.2	10.8	209.8	32.1	8540	58	40
36300220	VF 320/90R50		166D		TL	47	DW11	72.7	13.0	221.1	33.9	11670	64	40
36300100	IF 480/80R50	18.4R50	166D		TL	52	DW16B	80.2	18.9	242.2	37.0	11700	35	40
36350100	VF 480/80R50		169D		TL	52	DW16L	80.2	18.7	240.3	36.2	12780	29	40
36300017	VF 270/95R54	11.2R54	156D		TL	44	DW10	76.6	11.3	226.1	35.2	8800	52	40

## THE IF/VF ADVANTAGE

### MINIMIZE SOIL COMPACTION



VF Tire Standard Radial Tire

### STEEL BELTED




### UNIQUE TREAD DESIGN

Directional tread design provides high traction and lateral traction



- Larger contact area
- Smoother ride on the road
- Uniformed weight distribution



VISIT [YOKOHAMA-OHT.COM](http://YOKOHAMA-OHT.COM) FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit [www.yokohama-oht.com](http://www.yokohama-oht.com) or email us at [info@yokohama-oht.com](mailto:info@yokohama-oht.com).



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

