

MFS 101 SDS STEER YOUR WAY TO LONG-LASTING COMFORT

- Continuous center lug for a smooth ride
- Low vibration and improved shock absorption
- Extra usable tread above the 60J indicator for longer service life
- Circumferential grooves for improved steering
- Anti-slip steel beads help to avoid wheel slip



GALAXY MFS 101 SDS

OEM FITMENT

The Galaxy MFS 101 SDS is a new generation of solid tire, purpose-built to meet the needs of heavy-duty warehousing and industrial applications. It is designed to provide reduced vibrations, improved cushioning, and stability. Its three-stage construction, high wear resistance, and improved steerability make it an ideal workhorse for a variety of applications.



PRODUCT CODE	SIZE	TYPE	RIM TYPE	60J (IN)	PREFERRED RIM	OD (IN)	WIDTH (IN)	LOAD CAPACITY (LBS)					
								COUNTER BALANCE LIFT TRUCKS			OTHER VEHICLES		
								LOAD WHEEL	STEER WHEEL	MAX SPEED (MPH)	LOAD CAPACITY AT 4 MPH	LOAD CAPACITY AT 6 MPH	LOAD CAPACITY AT 16 MPH
110016	5.00-8	Solid	SH	58	3.00D-8	18	4.6	3119	2402	16	3119	2832	2402
110018	5.00-8	Solid	SH	58	3.75-8	18.0	4.6	3119	2402	16	3119	2832	2402
110008	15X4½-8	Solid	SH	40.3	3.00D-8	14.8	4.4	2292	1763	16	2292	2083	1763
110005	15X4½-8	Solid	SH	40.3	3.25I-8	14.8	4.4	2292	1763	16	2292	2083	1763
110026	16X6-8	Solid	SH	47.9	4.33R-8	16.4	6.0	3295	2535	16	3295	2997	2535
110004	18X7-8	Solid	SH	56.1	4.33R-8	17.8	6.0	4728	3637	16	4728	4287	3637
110006	140/55-9	Solid	SH	34.0	4.00E-9	14.8	5.1	2579	1984	16	2579	2336	1984
110020	6.00-9	Solid	SH	68.0	4.00E-9	20.8	5.3	4155	3196	16	4155	3769	3196
110030	21X8-9	Solid	SH	66.8	6.00E-9	20.6	7.2	6072	4672	16	6072	5510	4672
110032	180/60-10	Solid	SH	47.9	5.00F-10	18.1	6.3	5312	4077	16	5312	4805	4077
110022	200/50-10	Solid	SH	47.3	6.50F-10	18.0	7.6	5444	4188	16	5444	4937	4188
110024	6.50-10	Solid	SH	73.1	5.00F-10	22.7	6.2	5157	3967	16	5157	4684	3967
110041	23x9-10	Solid	SH	75.0	6.50F-10	23.0	7.8	7593	5841	16	7593	6888	5841
110039	7.50-10	Solid	SH	85.7	5.50F-10	24.9	7.6	6766	5201	16	6766	6138	5201
110037	23X10-12	Solid	SH	64.3	8.00G-12	23.0	9.2	8309	6392	16	8309	7538	6392
110034	27X10-12	Solid	SH	84.4	8.00G-12	26.6	9.5	8596	6612	16	8596	7802	6612
110071	23X5 (150/100-13)	Solid	SH	65.5	3.75P-13	24.5	5.4	3295	2535	16	3295	2975	2535
110050	7.00-15	Solid	SH	78.1	6.00-15	28.8	7.0	7815	6008	16	7815	7088	6008
110043	7.50-15	Solid	SH	83.8	5.50-15	29.8	7.8	8596	6612	16	8596	7802	6612
110052	7.50-15	Solid	SH	83.8	6.50-15	29.8	7.8	8596	6612	16	8596	7802	6612
110001	250-15	Solid	SH	75.6	7.00-15	28.3	8.7	10458	8045	16	10458	9499	8045
110009	250-15	Solid	SH	75.6	7.50-15	28.3	8.7	10458	8045	16	10458	9499	8045
110060	8.25-15	Solid	SH	97.7	6.50-15	32.2	8.3	10469	8045	16	10469	9477	8045
110058	300-15	Solid	SH	98.3	8.00-15	32.4	10.1	12893	9918	16	12893	11703	9918
110056	355/65-15	Solid	SH	99.5	9.75-15	32.5	12.3	17191	13224	16	15615	14172	12012



Comfortable Ride
Continuous center lug



Even Wear and Load Distribution
Wide, flat tread



High Machine Stability
Wide, flat profile



Improved Steering
Circumferential grooves

VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

facebook.com/yokohamaohta

[@yokohamaohta](https://twitter.com/yokohamaohta)

yohta-blog.yokohama-oht.com

yokohama-oht.com